




# BROWNING BEARING COMPANY



30 mm x 55 mm x 9 mm skf 16006 bearing

Bearing No. 16006

16006 Bearing 2D drawings and 3D CAD models

Size	55x30x9 mm
Bore Diameter	55 mm
Outer Diameter	30 mm
Width	9 mm
d	30 mm
D	55 mm
B	9 mm
d <sub>1</sub>	37.7 mm
D <sub>1</sub>	47.3 mm
r <sub>1,2</sub> - min.	0.3 mm
d <sub>a</sub> - min.	32 mm
D <sub>a</sub> - max.	53 mm
r <sub>a</sub> - max.	0.3 mm
Basic dynamic load rating - C	11.9 kN
Basic static load rating - C <sub>0</sub>	7.4 kN
Fatigue load limit - P <sub>u</sub>	0.31 kN
Reference speed	28000 r/min
Limiting speed	17000 r/min
Calculation factor - k <sub>r</sub>	0.02
Calculation factor - f <sub>0</sub>	15
Category	Single Row Ball Bearings
Inventory	31.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.094



## BROWNING BEARING COMPANY

EAN	7316576676635
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	30MM Bore; 55MM Outside Diameter; 9MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	16006
Weight / LBS	0.207
Outer Race Width	0.354 Inch   9 Millimeter
Outside Diameter	2.165 Inch   55 Millimeter
Bore	1.181 Inch   30 Millimeter
bore diameter:	30 mm
static load capacity:	7.35 kN
outside diameter:	55 mm
precision rating:	Not Rated



## BROWNING BEARING COMPANY

overall width:	9 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	9 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.3 mm
snap ring included:	Without Snap Ring
maximum rpm:	17000 RPM
internal clearance:	C0
series:	16
dynamic load capacity:	11.9 kN
$d_1$	37.7 mm
$D_1$	47.3 mm
$r_{1,2}$ min.	0.3 mm
$d_a$ min.	32 mm
$D_a$ max.	53 mm
$r_a$ max.	0.3 mm
Basic dynamic load rating C	11.9 kN
Basic static load rating $C_0$	7.35 kN
Fatigue load limit $P_u$	0.31 kN
Calculation factor $k_r$	0.02
Calculation factor $f_0$	15
Mass bearing	0.089 kg