



BROWNING BEARING COMPANY



20 mm x 47 mm x 14 mm skf 6204 etn9 bearing

Bearing No. 6204 etn9

6204 etn9 Bearing 2D drawings and 3D CAD models

Size	47x20x14 mm
Bore Diameter	47 mm
Outer Diameter	20 mm
Width	14 mm
d	20 mm
D	47 mm
B	14 mm
d ₁	28.2 mm
D ₁	39.6 mm
r _{1,2} - min.	1 mm
d _a - min.	25.6 mm
D _a - max.	41.4 mm
r _a - max.	1 mm
Basic dynamic load rating - C	15.6 kN
Basic static load rating - C ₀	7.6 kN
Fatigue load limit - P _u	0.325 kN
Reference speed	32000 r/min
Limiting speed	20000 r/min
Calculation factor - k _r	0.025
Calculation factor - f ₀	12
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.093



BROWNING BEARING COMPANY

EAN	7316576628511
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Polyamide
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	20MM Bore; 47MM Outside Diameter; 14MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Polyamide Cage
Other Features	Deep Groove Reinforced Ball Set
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Weight / LBS	0.234
Outer Race Width	0.551 Inch 14 Millimeter
Bore	0.787 Inch 20 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	1.85 Inch 47 Millimeter
d ₁	28.2 mm



BROWNING BEARING COMPANY

D_1	39.6 mm
$r_{1,2}$ min.	1 mm
d_a min.	25.6 mm
D_a max.	41.4 mm
r_a max.	1 mm
Basic dynamic load rating C	15.6 kN
Basic static load rating C_0	7.65 kN
Fatigue load limit P_u	0.325 kN
Calculation factor k_r	0.025
Calculation factor f_0	12
Mass bearing	0.098 kg