



BROWNING BEARING COMPANY



1206 ektn9 Bearing 2D drawings and 3D CAD models

30 mm x 62 mm x 16 mm skf 1206 ektn9 bearing

Bearing No. 1206 ektn9

Category	Self Aligning Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.221
EAN	7316576624650
Product Group	B00152
Mounting Method	Tapered Adapter
Enclosure	Open
Rolling Element	Ball Bearing
Adapter Sleeve	H-206
Cage Material	Polyamide
Precision Class	ABEC 1 ISO P0
Internal Clearance	C0-Medium
Number of Rows of Balls	Double Row
Other Features	Allowable Misalignment 2.5 Deg High Capacity Design 1:12 Taper
Long Description	30MM Bore; Tapered Adapter Mount; 62MM Outside Diameter; 16MM Inner Race Width; 16MM Outer Race Width; Open; Polyamide Cage; Double Row of Balls; ABEC 1 ISO P0; C0-Medium
Inch - Metric	Metric
Category	Self Aligning Ball Bearings
UNSPSC	31171532



BROWNING BEARING COMPANY

Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Self Aligning
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	1206 EKTN9
Weight / LBS	0.485
Inner Race Width	0.63 Inch 16 Millimeter
d	1.181 Inch 30 Millimeter
Outer Race Width	0.63 Inch 16 Millimeter
D	2.441 Inch 62 Millimeter
bore diameter:	30 mm
precision rating:	Not Rated
outside diameter:	62 mm
maximum rpm:	15000 RPM
overall width:	16 mm
cage material:	Fiberglass Reinforced Nylon
bore type:	Tapered 1:12
finish/coating:	Uncoated
closure type:	Open
maximum misalignment:	2.5 °
internal clearance:	C0
outer ring width:	16 mm
dynamic load capacity:	15.6 kN
fillet radius:	1 mm
static load capacity:	4.65 kN
series:	1200
d	30 mm
D	62 mm
B	16 mm
d ₁	40.3 mm
D ₁	51.9 mm
r _{1,2} min.	1 mm



BROWNING BEARING COMPANY

D_a max.	56.4 mm
r_a max.	1 mm
Basic dynamic load rating C	15.6 kN
Basic static load rating C_0	4.65 kN
Fatigue load limit P_u	0.24 kN
Reference speed	24000 r/min
Limiting speed	15000 r/min
Permissible angular misalignment	2.5 °
Calculation factor k_r	0.04
Calculation factor e	0.25
Calculation factor Y_0	2.5
Calculation factor Y_1	2.5
Calculation factor Y_2	3.9
Mass bearing	0.22 kg